MODEL NO.	LMD17S19B1B25-080	DWG NO.	A6662

CUSTOMER'S MODEL: NO MODEL
END COVER COLOR: BLACK

REV.	REVISION RECORD	BY	DATE
0	ORIGIN	LJ	4.13.2026





PHOTOELECTRIC SWITCH SEQUENCE		
PIN NO	BIPOLAR	LEADS
1	+5~24V	BRN
2	GND	BLU
3	SIGNAL LINE	BLK
4	N/A	WHT

MOTOR CONNECTION			
PIN NO	BIPOLAR	LEADS	WINDING
1	A+	RED	A+
2	A -	RED/WHT	A-
3	B+	GRN	B+ B-
4	B -	GRN/WHT	

SPECIFICATION \ CONNECTION	BIPOLAR
AMPS/PHASE	2.50
RESISTANCE/PHASE(Ohms)@25°C	0.80±10%
INDUCTANCE/PHASE(mH)@1KHz	1.80±20%
HOLDING TORQUE(Nm)[Ib-in]	0.5[4.43]
MAXIMUM THRUST(N)	135
STEP ANGLE(°)	1.80
STEP ACCURACY(NON-ACCUM)	±5.00%
LEAD(mm)[in]	10[0.3937]
LINEAR TRAVEL/STEP(mm)[in]	0.05[0.0019685]
RATED LOAD CAPACITY(N)	115
MAX SPEED(mm/s)	300
POSITION ACCURACY(mm)	±0.02
AMBIENT TEMPERATURE	-20°C~50°C[-4°F~122°F]
INSULATION CLASS	B 130°C[266°F]
TEMPERATURE RISE	MAX.80°C

COMMENT:
1.TMBF 6000h OR MORE @ 24V/300RPM
2.INSULATION RESISTANCE
(NORMAL TEMPERATURE AND HUMIDITY): 100 Mohm
3.DIELECTRIC STRENGTH 500VAC FOR 1MIN.
(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)

FULL STEP 2 PHASE-Ex.,WHEN FACING MOUNTING END (X)

STEP	A+	B+	A-	B-	↓ CW	↑ CCW
1	+	+	-	-		
2	-	+	+	-		
3	-	-	+	+		
4	+	-	-	+		

DIMENSIONS ARE IN MILLIMETERS.
TOLERANCES AS BELOW:

DECIMALS		ANGLES
X	±0.5	±2°
X.X	±0.25	
X.XX	±0.13	

THIRD ANGLE PROJECTION

THIS DOCUMENT SHALL NOT BE REPRODUCED NOR SHALL THE INFORMATION CONTAINED HEREIN BE USED BY OR DISCLOSED TO OTHERS UNLESS EXPRESSLY AUTHORIZED IN BY WRITING STEPPERONLINE.

	SIGNATURE	DATE
DRN	LJ	4.13.2026
APVD	ZPJ	4.13.2026

STEPPERONLINE®

LINEAR ACTUATORS

LMD17S19B1B25-080

REV.	0	SCALE	1:1	DWG NO.	A6662